


"5VX" SECTION LIST (17 x 14 mm)

Available Sizes:

240	710	900	1060	1180	1250	1900
500	750	1000	1080	1220	1320	2000
700	800	1030	1120	1230	1800	



"PJ" SECTION LIST

Available Sizes:

483	660	864	1054	1143	1245	1346	1549	1854	1994	2337
508	711	914	1092	1168	1270	1372	1588	1892	2083	2388
559	724	940	1105	1194	1283	1397	1651	1905	2210	2438
584	762	965	1118	1219	1295	1422	1664	1956	2261	2489
610	813	1016	1130	1232	1308	1473	1753	1969	2286	2540

"PK" SECTION LIST

Available Sizes:

610	711	927	1054	1257	1425	1930	2300
660	762	940	1080	1295	1461	1981	2540
686	902	991	1194	1334	1626	2000	
699	914	1016	1229	1359	1829	2100	

"PL" SECTION LIST

Available Sizes:

1270	1473	1803	2070	2324	2743	3086	3696	5029	7645	12217
1334	1562	1842	2096	2362	2845	3124	4051	5385	8407	13741
1372	1613	1943	2134	2477	2896	3289	4191	6096	9169	13970
1397	1664	1981	2197	2515	2921	3327	4470	6121	9931	13995
1422	1715	2019	2235	2705	2997	3493	4623	6883	10639	

"PM" SECTION LIST

Available Sizes:

2311	2832	3327	4191	5410	8407	12217
2388	2921	3531	4470	6121	9169	13741
2515	3010	3734	4648	6883	9931	13970
2692	3124	4089	5029	7645	10693	13995

► DUNLOHIFLEX



DUNLOHIFLEX

DINLOHIFLEX belts are built to the highest standards from the best materials available using state of the art manufacturing processes.

Construction & Features

Stiff yet flex crack resistant base made out of specially compounded polymers ensures uniform land transfer to cords preventing power loss and premature belt failure.

The High Modulus Low Stretch HMLS Polymer Cords enable the belts to carry higher horse power loads with minimum stretch resulting in better belts stability and fewer take up adjustments.

Specially Designed polyester cotton blended fabric jacket impregnated with Polychloroprene synthetic rubber Imparts superior flexiblty, better traction, flex and wear resistance. This makes the belts oil and heat resistant as well as antistatic.

DUNLOHIFLEX belts are 'Precision Built' and subject to precise length stability and hence, no need for matching of belts.

even almost a group of belts which were nominally of the same length. This was due to the nature of material - textiles and polymers used and the technology adopted.

These belts of superior length stability, evenly tensioned, take higher loads for longer periods resulting in maximum belt life.



DUNLOHIFLEX



HIGH PERFORMANCE
EXCELLENT PRICE

Canada Office:

Contact: +1-587-581-1777 | Email: sales@choksiindustries.com | URL: www.choksiindustries.com

"AX" SECTION (13 x 8 mm)

Available Sizes:

23	28	33	38	43	48	53	58	63	68	73	79	84	89	94
24	29	34	39	44	49	54	59	64	69	74	80	85	90	95
25	30	35	40	45	50	55	60	65	70	75	81	86	91	96
26	31	36	41	46	51	56	61	66	71	76	82	87	92	97
27	32	37	42	47	52	57	62	67	73	77	83	88	93	98



"BX" SECTION (17 x 11 mm)

Available Sizes:

21	27	33	39	45	51	57	66	78	90
22	28	34	40	46	52	58	68	80	92
23	29	35	41	47	53	59	70	82	94
24	30	36	42	48	54	60	72	84	96
25	31	37	43	49	55	62	74	86	98
26	32	38	44	50	56	64	76	88	99



"CX" SECTION (22 x 14 mm)

Available Sizes:

25	31	37	43	49	55	61	67	73	79	85	91	97
26	32	38	44	50	56	62	68	74	80	86	92	98
27	33	39	45	51	57	63	69	75	81	87	93	99
28	34	40	46	52	58	64	70	76	82	88	94	
29	35	41	47	53	59	65	71	77	83	89	95	
30	36	42	48	54	60	66	72	78	84	90	96	



"XPZ" SECTION (10 x 8 mm)

Available Sizes:

590	850	1000	1400	1700	2000
750	900	1250	1500	1800	3000
800	950	1320	1600	1900	5117



"XPA" SECTION (13 x 10 mm)

Available Sizes:

590	1180	1320	1500	1700	2000
950	1250	1400	1600	1900	5117



"XPB" SECTION (17 x 14 mm)

Available Sizes:

600	2120	2500	2800	3350	4500
2000	2360	2650	3000	3550	5140



"XPC" SECTION (22 x 18 mm)

Available Sizes:

600	2000	2360	3000	3750	4500
1000	2120	2650	3350	4000	4750
1500	2240	2800	3550	4250	5163



"3VX" SECTION (9.7 x 8 mm)

Available Sizes:

475	630	1180	1400	1800
500	800	1250	1500	1900
560	1000	1320	1600	2020



"SPZ" SECTION (10 x 8 mm)

Available Sizes:

600	800	962	1100	1240	1380	1520	1675	1837	2000	2140	2360	2840
630	825	975	1120	1262	1400	1537	1700	1850	2020	2160	2380	3000
670	850	1000	1140	1280	1420	1560	1720	1880	2037	2175	2400	3150
700	875	1020	1160	1300	1440	1580	1740	1900	2060	2187	2500	3350
722	900	1040	1180	1320	1460	1600	1762	1930	2082	2200	2540	3550
750	920	1060	1200	1340	1480	1625	1787	1950	2100	2240	2650	3750
775	940	1080	1220	1360	1500	1650	1800	1975	2120	2300	2800	



"SPA" SECTION (13 x 10 mm)

Available Sizes:

576	925	1032	1175	1300	1425	1600	1782	1943	2132	2332	2607	2900
725	932	1060	1180	1307	1432	1625	1800	1950	2180	2360	2632	2932
732	950	1082	1187	1320	1450	1632	1818	1957	2182	2382	2650	2982
782	967	1090	1207	1332	1457	1650	1832	1982	2200	2430	2682	3000
800	975	1100	1220	1337	1482	1657	1850	2000	2207	2432	2720	3030
825	982	1107	1232	1360	1500	1682	1857	2020	2240	2482	2732	3082
850	992	1120	1250	1375	1532	1700	1882	2057	2280	2500	2750	3150
875	1000	1132	1275	1382	1550	1732	1900	2060	2282	2532	2782	3350
882	1025	1150	1280	1400	1557	1750	1925	2082	2300	2580	2800	3550
900	1030	1157	1282	1418	1582	1757	1932	2120	2310	2582	2832	3750



"SPB" SECTION (17 x 14 mm)

Available Sizes:

940	1340	1700	2150	2530	2840	3550	4060	5000	6300
1000	1400	1800	2240	2560	2850	3650	4250	5070	6340
1120	1500	1900	2280	2600	3000	3750	4310	5300	6700
1250	1550	2000	2360	2680	3150	3800	4500	5600	7100
1260	1560	2020	2410	2730	3170	3825	4560	5680	7500
1320	1600	2120	2500	2800	3350	4000	4750	6000	8000



"SPC" SECTION (22 x 18 mm)

Available Sizes:

1700	2060	2240	2800	3550	4400	5000	6000	7500	9500	11800
1750	2100	2360	3000	3750	4500	5300	6300	8000	10600	12500
2000	2120	2500	3150	4000	4700	5480	6700	8500	11000	12800
2050	2150	2650	3350	4250	4750	5600	7100	9000	11200	



"3V" SECTION (9.7 x 8 mm)

Available Sizes:

710	850	1000	1180	1400	1660
750	900	1060	1200	1500	
800	950	1120	1320	1600	



"8V" SECTION (25.5 x 22 mm)

Available Sizes:

1000	1200	1500	1800	2120	2550	3150	4000	6640
1060	1250	1600	1850	2240	2800	3350	4500	
1120	1320	1700	1900	2360	2900	3550	4750	
1180	1450	1750	2000	2500	3000	3750	5000	



"A" SECTION (13 x 8 mm)

Available Sizes:

18	29	40	51	62	73	84	95	106	117	128	139	175
19	30	41	52	63	74	85	96	107	118	129	140	180
20	31	42	53	64	75	86	97	108	119	130	142	185
21	32	43	54	65	76	87	98	109	120	131	144	
22	33	44	55	66	77	88	99	110	121	132	146	
23	34	45	56	67	78	89	100	111	122	133	148	
24	35	46	57	68	79	90	101	112	123	134	150	
25	36	47	58	69	80	91	102	113	124	135	155	
26	37	48	59	70	81	92	103	114	125	136	160	
27	38	49	60	71	82	93	104	115	126	137	165	
28	39	50	61	72	83	94	105	116	127	138	170	



"B" SECTION (17 x 11 mm)

Available Sizes:

21	31	41	51	61	71	81	91	101	111	122	142	180	230
22	32	42	52	62	72	82	92	102	112	124	144	185	235
23	33t	43	53	63	73	83	93	103	113	126	146	190	250
24	34	44	54	64	74	84	94	104	114	128	148	195	275
25	35	45	55	65	75	85	95	105	115	130	150	200	300
26	36	46	56	66	76	86	96	106	116	132	155	205	
27	37	47	57	67	77	87	97	107	117	134	160	210	
28	38	48	58	68	78	88	98	108	118	136	165	215	
29	39	49	59	69	79	89	99	109	119	138	170	220	
30	40	50	60	70	80	90	100	110	120	140	175	225	



"C" SECTION (22 x 14 mm)

Available Sizes:

36	45	54	63	72	81	90	99	116	134	130	148	190	235	290
37	46	55	64	73	82	91	100	118	136	132	150	195	240	295
38	47	56	65	74	83	92	102	120	138	134	155	200	245	300
39	48	57	66	75	84	93	104	122	140	136	160	205	250	320
40	49	58	67	76	85	94	106	124	142	138	165	210	255	340
41	50	59	68	77	86	95	108	126	144	140	170	215	260	
42	51	60	69	78	87	96	110	128	146	142	175	220	265	
43	52	61	70	79	88	97	112	130	126	144	180	225	270	
44	53	62	71	80	89	98	114	132	128	146	185	230	285	



"D" SECTION (32 x 19 mm)

Available Sizes:

75	98	114	119	158	173	195	220	240	280	328
88	100	115	120	162	180	200	225	250	298	358
90	108	116	128	165	185	204	230	268	300	370
95	109	118	144	168	190	210	238	270	314	390
						215				408



"E" SECTION (38 x 23 mm)

Available Sizes:

90	180	210	238	2
----	-----	-----	-----	---